Product Test Certificate

161350 Certificate Number

23/09/2016 Date

AUSTRALIAN PIPE & TUBE

PackFrom	PackTo	RHS/SHS/CHS Nominal Size (mm) d /do	b	t	L	Specification	Grade	Product Description
16259M10058	16263M10004	65.0	65.0	2.5	Any	AS1163: 2016	C350L0	Galvanised 65x65x2.5

Heat No.	Steel Supplier	Testing Authority/NATA (ILAC) No			Steel Chemical Analysis																Mechanical Test Results (Orientation-"L")									
		Tensile	Impact	Chemical	Analysis Type "L"/"P"	Testing Report No	C	P	Mn	Si	S	Ni	Cr	Mo	Cu	Al	Ti	Nb	V	B	CE	SiE	Testing Report No-Sample ID	Condition	Tensile Test			Impact Test at 0°C			
							(% x 100)																		YS	TS	E	1	2	3	Avg
																									MPa		%	Joules			
MP925	Import	MTL/19968		SS/19570	P	65237	19	2	78	1.1	<2	0.9	2	2	2	1	4.8	<1	<1	<1	35	6	T3316-7081	A	505	607	22				
MQ182	Import	MTL/19968		SS/19570	P	65237	20	1.6	84	1.4	<2	0.9	2	2	1	1	4.2	<1	<1	<1	35	6	T3316-7080	A	461	565	29				

Notes:

1) CE=C+Mn/6+(Cr+Mo+V)/5+(Ni+Cu)/15; **2)** SiE=Si+2.5P; **3)** Gauge Length for E= 5.65√So; **4)** Impact test piece thickness is 5 mm;

5) For t less than 6 mm L0 properties derived as per Cl 9.4.2.3 (b) of AS/NZS 1163; **6)** "L" = LADLE, "P" = PRODUCT

7) ALS=Australian Laboratory Services Industrial; MTL = Mec Test Laboratories; SS=Spectrometer Services Pty Ltd; BSL=Bluescope Steel;

8) The production date in the format yyddd constitutes the first 5 digits of the pack number and is printed on each length;

9) THE STEEL IS MADE BY BASIC OXYGEN OR AN ELECTRIC ARC PROCESS AND IS FULLY KILLED, CONTINOUSLY CAST AND FINE GRAINED. THE STRIP WAS HOT ROLLED AT THE HOT STRIP MILL.

Product Test Certificate

161350 Certificate Number

23/09/2016 Date

Packs covered by this certificate

Heat	Pack Numbers
MQ182	16259M10058 16259M10059 16259M10060 16259M10062 16259M10063 16263M10001 16263M10002
MP925	16259M10060 16259M10061 16259M10062 16263M10002 16263M10003 16263M10004

Australian Pipe and Tube confirms that products listed above were manufactured, tested, and supplied in full compliance with the specifications quoted in this certificate.

Authorized signatory: L. DONALD

CEO